



\* Punaisella merkityt varastotuotteita. Muut tilauksesta.

Alusta 3500 KG							
Til.No.	Mitta A	Mitta C	Pulttijako	Omapaino (ilman pyöriä)	Lavakoko max. (pyörien väliin)	pyörä 1	pyörä 2 (Vaihtoehto)
22999	1200	1670	5x112	281	1350x5000	195R14C8	195/55R13
22999	1500	1970	5x112	287	1650x5000	195R14C8	195/55R13
22999	1600	2070	5x112	289	1750x5000	195R14C8	195/55R13
22117	1700	2170	5x112	291	1850x5000	195R14C8	195/55R13
22118	1800	2270	5x112	293	1950x5000	195R14C8	195/55R13
22119	1900	2370	5x112	295	2050x5000	195R14C8	195/55R13

Radbremse	250x40 RAK (25-2025)
Radanschluß	5 Radschrauben M12x15 Kugelbund (5/-/112)
Ausführung	Aggregat verzinkt

**H&F NIEPER** GmbH & Co  
Achsenfabrik Solingen

Bearb.	18.03.11	Name	FHE
Gepr.			
Norm			

Zust. Änderung Datum Name

Maßstab	1: 15 (110 ; 15) (A3)	Gewicht	
Werkstoff			
Benennung	Gummifeder-Fahrgestell GF 3500		
Zeichnungsnummer	GF351902	Blatt	BL